

Labelprinter

model BP-700

THE PERFECT SOLUTION FOR DIRECT THERMAL APPLICATIONS.



Properties

- thermal labelprinter connectable to weight indicator i.a. HP-Touch
- easy replacement of the label roll
- print methode: direct
- resolution 203 dpi
- paper width up to max. 114 mm, roll diameter externally up to 200 mm
- print speed up to 304 mm / sec.
- fonts: Times Roman (6 sizes), Helvetica (6 sizes), Presentation (1 size), Letter Gothic (1 size), Prestige Elite (2 sizes), Courier (2 sizes), OCR (2 sizes), Gothic (1 size), Outline font (4 types), Price font (3 types)
- barcode printing, i.a.: EAN8, EAN8+2 digits, EAN8+5 digits, EAN13, EAN13+2 digits, EAN13+5 digits, UPC-E, UPC-E+2 digits, UPC-E+5 digits, UPC-A, UPC-A+2 digits, UPC-A+5 digits, MSI, CODE39, CODE93, CODE128, EAN128, Industrial 2 to 5, Customer Bar Code
- equipped with LCD-display 128x64 dots
- sturdy metal anti-static housing
- dimensions 278 (w) x 460 (d) x 310 (h) mm
- weight: 17 kg
- operating temperature 5 - 40 °C
- power: external adapter 240V
- options: Wifi LAN, parallel, serial, expansion I/O, RTC & USB host

Note: If the printer is connected to a verified scale it is not possible to print if the weight is under the legal minimum weight of the balance to weigh.

