

# Electronic weigh indicator

## model IND-II



### Technical data

Input sensitivity	0.2µV/DIV
Input voltage range	-0.2mV to 20mV
Display	backlit LCD, 6 characters 31 mm high
Qty of connectable load cells	up to 8 load cells of 350 Ω (120 mA)
Non-linearity	0.007 % from total capacity
Input impedance	10 MΩ or higher
A/D conversion mode	Δ-Σ
A/D internal resolution	700000 div
A/D conversion speed	10 x / sec
External display resolution	15000 div
Number of LCD digits	6
Number of keys	9
Power	- AC 110V/230V (AC±10%) - internal rechargeable battery (6V/4A) + internal charger

### General properties

- application not for legal trade
- smooth, easy to clean plastic housing, supplied with clear transparent protection hood
- large, clearly backlit and easy readable 6 characters LCD-display, 31 mm height
- water protected keypad, 9 function keys
- automatic zero setting
- filter for speed setting, adjustable according to environment conditions
- weight units: kg, g and pieces
- resolution 1/15000
- functions : tare, preset tare, simple piece counting, check weighing, accumulated weighing, peak hold.
- power: internal rechargeable battery 6V/4A; internal charger 230V
- solid net cord with socket for internal charger
- automatic power off selection; low battery indication
- dimensions 274 x 170 x 117 mm