

# Precision balance

Multifunctional high capacity precision balance suitable for use both in the laboratory and in industrial environment

## serie IPB



### Properties

- version: CE-approvable
- large, clearly readable green 8 digit LED-display
- very robust version in full stainless steel housing, protection class **IP65**
- stainless steel weigh platform 350 x 400 mm (w x d)
- waterproof membrane keypad with 10 keys
- indicator equipped with 2 indication LEDs for active functions indication
- equipped with 4 adjustable feet and level
- supplied with clear transparent dust cover for the keyboard
- indicator mounted at the frame (model IPB), or separate, equipped with approx. 1 m cable (model IPB-K) for installation on a table or mounted at the wall
- functions: tare, zero setting, piece counting and percentage weighing
- equipped with RS-232 interface for connection to PC or printer
- weigh units (only settable for non-approved models): g, kg, lb, oz, ct, ozt and dwt
- power: 230V adapter (incl.)

### Options a.o.

- thermal ticketprinter AS-310
- antivibration table
- weigh below hook
- RS-232 cable to PC

type	IPB-22	IPB-33	IPB-K-22	IPB-K-33	IPB-22-M	IPB-33-M	IPB-K-22-M	IPB-K-33-M
capacity	22 kg	33 kg	22 kg	33 kg	22 kg	33 kg	22 kg	33 kg
division e*	-	-	-	-	1 g	1 g	1 g	1 g
division d*	0.1 g	0.1 g	0.1 g	0.1 g	1 g	1 g	1 g	1 g
platform dim.	350 x 400 mm (w x d)							
version	not for legal trade				<b>M</b> CE-verified			
indicator	at front side		separate with 1 m cable		at front side		separate with 1 m cable	

\* division e = approved unit  
indeling d = reading unit

