

Weighing hand pallet truck



Suitable for application in ATEX hazardous area, protection according to **ATEX II 2GD IIB T4 T197°C Zone 1 and 22 & 22 and 2**



model PT 2GD

General data

- **CE verified** (dual range* division PT2 GDM; triple range PT 2GD not for legal trade)
- flat, water protected keypad, 17 keys
- LCD display with 6 25-mm high contrast digits, clearly visible even in poor lighting conditions and with low temperatures, and with symbols for showing the active functions
- satined stainless steel housing **IP68**, dimensions 264 x 174 x 115 mm
- tare function, preset tares; several operating functions, cumulative weighing, check weighing, piece counting, recipe weighing, percentage determination, in/out truck weighing
- very rigid, stove enamelled steel basic construction
- steering wheels and double loading rollers with a polyurethane coating
- 4 stainless steel shear-beam load cells IP68
- capacity 2000 kg; own weight 125 kg
- lifting height 85 - 200 mm
- fork dimensions: 1170 x 180 mm
- inner width between the forks 190 mm; outer width 550 mm
- height from floor to display top 885 mm
- internal rechargeable battery, approx. 150 h. operating time on fully charged battery
- included battery charger (application in safe area)

Options

- real-time clock module (date/time)
- alibi memory incl. date/time for max. 120.000 weighings
- stainless steel forks
- parking brake system with command pedal mounted on steering wheels

* With dual range division reading within the first part (1) of the capacity is 2x / 2,5x more accurate than within the second part (2). With triple range division reading within the first part (1) of the capacity is 2,5x more accurate than within the second part (2); within the second part of the capacity reading is again 2x more accurate than within third part (3).

type	PT 2GD (triple range)	PT 2GDM (dual range)
capacity	2000 kg	2000 kg
division 1*	0-500 kg: 0,2 kg	0-1000 kg: 0,5 kg
division 2*	500-1000 kg: 0,5 kg	1000-2000 kg: 1 kg
division 3*	1000-2000 kg: 1 kg	n.a.
CE approval	not for legal trade	M CE-approved