

# Weighing hand pallet truck



Suitable for application in ATEX hazardous area,  
protection according to **ATEX II 3GD IIC T6**  
**T130°C X (ZONE 2, 22)**



\* With dual range division reading within the first part (1) of the capacity is 2x / 2,5x more accurate than within the second part (2). With triple range division reading within the first part (1) of the capacity is 2,5x more accurate than within the second part (2); within the second part of the capacity reading is again 2x more accurate than within third part (3).

## model PT 3GD

### General data

- **CE approvable** (dual range\* division PT3 GDM; triple range\* PT 3GD not for legal trade)
- indicator in satined stainless steel housing IP68
- incorporated, backlit LCD display, character height 25 mm
- flat, water protected keypad, 16 keys
- tare function, preset tares; several operating functions, cumulative weighing, checkweighing, recipe weighing, percentage determination, piece counting, in/out truck weighing
- very rigid, stove enamelled steel basic construction
- steering wheels and double loading rollers with a polyurethane coating
- 4 RVS shear-beam load cells IP68
- capacity 2000 kg; own weight 120 kg
- lifting height 85 - 200 mm
- fork dimensions: 1170 x 180 mm
- inner width between the forks 190 mm; outer width 550 mm
- height from floor to display top 885 mm
- internal rechargeable battery, approx. 40 h. operating time on fully charged battery
- inclusive battery charger (application in safe area)

### Options

- real time clock
- alibi memory with date/time, up to 120.000 weighings
- stainless steel forks in stead of stove enamelled steel
- parking brake, mounted on steering wheels

| type        | PT 3GD (triple range) | PT 3GDM (dual range) |
|-------------|-----------------------|----------------------|
| capacity    | 2000 kg               | 2000 kg              |
| division 1* | 0-500 kg: 0,2 kg      | 0-1000 kg: 0,5 kg    |
| division 2* | 500-1000 kg: 0,5 kg   | 1000-2000 kg: 1 kg   |
| division 3* | 1000-2000 kg: 1 kg    | n.v.t.               |
| CE approval | not for legal trade   | <b>M</b> CE-approved |

