

Small Livestock Veterinary Scale model **HMV1**

Mobile livestock weigher, versatile. Available in aluminum version which is light in weight and a galvanized version which is extra robust.



HMV1-steel

HMV1-alu



HMV1-steel



HMV1-alu

Properties

- version CE approvable (application for legal trade)
- capacity 300 kg, division per 0.1 kg or 0.5 kg (the division per 0.5 kg gives a stable display more quickly)
- Available in two different versions:
 - **HMV1-alu**: fencing, base frame and tear plate base made entirely of aluminum
 - **HMV1-steel**: fencing, base frame and tear plate base made entirely of galvanized steel, robust design
- exterior opening door at both short sides; operated from 1 side
- easily movable by 2 handles and 2 wheels on short sides
- weighing indicator with LCD-display ISC-V in stainless steel housing, protection class IP68, mounted at the frame
- functions: animal weighing program for stable indication; full range tare, high resolution displaying (10x more accurate) net/gross weight or lb/kg, accumulate, check weighing, hold- and peak function
- equipped with 1x RS232/C / RS485 interface for connection to PC, PLC etc.
- equipped with 1x RS232/C interface for connection to (label)printer
- including IR input for optional remote control
- overall dimensions 166 x 60 x 96/144 cm (l x w x h-cage/h-indicator), inner dimensions weighing cage 141 x 51 x 86 cm (l x w x h)
- power: 230V, solid mains cord (optionally available with internal rechargeable battery)

Options i.a.

- external thermal ticketprinter/labelprinter
- separate pole for indicator
- easy weigh software for Windows
- connection cable from RS-232 to PC/printer
- wireless connection indicator (RS-232) to USB of PC / printer
- pit frame for permanent installation in the floor

type	HMV1-alu-100	HMV1-alu-500	HMV1-staal-100	HMV1-staal-500
capacity	300 kg	300 kg	300 kg	300 kg
division	0.1 kg	0.5 kg	0.1 kg	0.5 kg
N. platform dim.	141 x 51 cm			

HMV1 measurement sketch (dimensions in mm)

